Palma

Design by Antoni Arola.



3734.

Application

Hanging lamps

Installation type

Surface

Description

Nature takes control of the space. With the pendant lamps the interior ambience takes on a life of its own with the possibility of integrating plants with the lighting compositions.

Diffuser

Blow-glass diffuser

Materials

Profile: Aluminum Diffuser: Blown-glass

Flowerpot: PMMA (thermoplastic polymer)


Finish



3734-18 Graphite (ADAPTA RF 9913 WX)

3734-93 White (RAL 9016)

Sketch



Electrical characteristics

2 x LED 4,6W 500mA AND

1 x LED 2W 500mA



Total 11.2 W







Light source: 2700K CRI >90 Fixture: 1371.09 lm 67.21 lm/W

Driver included: CC - Constant Current 500 mA 110~240V 50/60Hz

Electronic dimming DALI 1-10V Push Optional dimming: Casambi

Technical characteristics

- Plants not included

Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.1790 m³ / Gross weight 9.5 kg. / Net weight 6.0 kg.

Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency: 1 Coordinate system : CG Total flux: 1301.84 lm

Maximum value : 66.04 cd/klm Light position : C=0.00 G=1.00 Symmetry on the planes : Asymmetric Isolux: Isolux (Floor) Light position: X=0.00m Y=0.00m Z=2.50m

Certificates













